

PRODUCT DESCRIPTION:

A high quality, versatile acrylic polymer primer, suitable for interior and exterior concrete, brick or stucco surfaces which are chalky or soft.

PRODUCT FEATURES:

- Excellent bonding properties
- Excellent adhesion to chalky or previously coated substrates
- Excellent freeze thaw properties and flexibility in extreme temperatures
- Fast drying, quick recoat time
- Excellent adhesion to surfaces that are normally difficult to bond to.
- Low odour

TYPICAL USES:

- Ideal primer for concrete surfaces that are porous, or have old coating on them.
- Improves the bond of Liquistone to most surfaces.
- Acts as a binder for chalky surfaces such as old clay bricks.
- Provides superb adhesion between old or repaired stucco and other NPC coatings

SURFACE PREPARATION:

Consult NPC representative for appropriate preparation methods for specific applications and environments.

Hand tool cleaning, water blasting and proper surface profile must all be considered when using **ACRYLIC STONE BINDER** in high performance applications.

All surfaces to be coated must be free of rust scale, dirt, oils, laitance and any other contaminants that may prevent proper adhesion.

TECHNICAL DATA

| | |
|--------------------------------------|--|
| COLOUR: | Milky White |
| RESIN TYPE: | 100% Acrylic Solution |
| PERCENT SOLIDS by WEIGHT: | 32% |
| RECOMMENDED COVERAGE: | 200-400 sqft/US Gal depending on the porosity of the substrate. |
| VISCOSITY: | 70 cps |
| DRY TIME @20°C(68°F): | Dust free - 30 minutes Touch Dry - after 1-2 hours Recoat time – 1-2 hours |
| REDUCER: | Clean Water |
| CLEAN UP: | Water |
| APPLICATION: | Conventional Spray, Airless Spray, Brush and Roller. |

NOTE: The above data is solely based on lab testing done under strictly controlled conditions. Ambient temperature was used for all testing. No warranty can be given as to the accuracy of this information as it will depend upon conditions at actual project locations, which are beyond our control.