

EXTERIOR FLOOR GLAZE

PAGE 1 OF 1

PRODUCT DESCRIPTION:

EXTERIOR FLOOR GLAZE is a single-component clear acrylic coating. Formulated to withstand the extreme conditions of interior and exterior service such as exposure to U.V. sunlight as well as temperature fluctuations.

PRODUCT FEATURES:

- Fast drying and easy to apply.
- Will not break down or yellow with exposure to U.V. light
- Abrasion resistant , will stand up to heavy foot traffic as well as light to medium duty vehicular traffic
- Excellent chemical resistance to salts, acids,alkalis, detergents, oils and fats
- Flexible, unaffected by temperature fluctuations and thermal shock
- Non-staining and scrubbable

TYPICAL USES:

- Seals interior and exterior concrete and masonry (eg.concrete or interlocking brick driveways,walkways, stamped concrete, acid stains, polymer concrete overlays.)
- Cure and Seal for concrete.
- Exterior finish coat for NPC flooring systems (ie. Kromotex, Kromoquartz).

APPLICATION:

- Self-priming on bare concrete or masonry.

- Applied by brush, roller or sprayer(airless or air spray)

TECHNICAL DATA

COLOUR:	Clear
SHEEN:	Gloss
VOLUME SOLIDS:	40%
THEORETICAL COVERAGE:	642 sqft/ US Gal @ 1 mil DFT
RECOMMENDED DFT:	approx. 2-4 mils/ coat
DRY TIME: @21°C(70°F)	Touch 1-2 hrs Light Traffic 24 hrs Normal Traffic 7 days
FLASH POINT:	27°C(81°F)
REDUCER:	NPC Glaze Thinners
CLEAN UP:	NPC Glaze Thinners

SURFACE PREPARATION:

Bare Concrete:

Ensure surface is clean, dry, porous and free of any contaminants. Oil and grease should be removed by cleaning with xylene or commercial degreasers. For an ideal surface profile, mechanical abrasion is recommended.

Previously Painted Concrete:

EXTERIOR FLOOR GLAZE will likely cause wrinkling or bubbling when it comes in contact with an oil-based paint. Removal is recommended. If the compatibility of the existing paint is in question, test a small

EXTERIOR FLOOR GLAZE

PAGE 1 OF 1

section and check for lifting. Hard or glossy surfaces should be abraded to improve adhesion performance.