

## PRODUCT

### DESCRIPTION:

WB ENAMEL is an acrylic, water-based paint intended for interior and exterior use wherever an enamel-like finish is required. Designed as an alternative to oil-based paint, it possesses all of its benefits while without sacrificing the advantages inherent in high-quality, water-borne acrylic paints.

### PRODUCT FEATURES:

- Excellent gloss retention
- Good hardness development, yet flexible
- V.O.C. compliant
- Alkyd-like application properties
- Low odour
- Early tack-free time
- Excellent flow and leveling
- Excellent adhesion to many surfaces
- Excellent colour stability including resistance to yellowing
- Scrubable and stain resistant
- Resistant to mildew growth

## PRODUCT

### LIMITATIONS:

- Not recommended for use on floors where water ponding or puddling is expected

### TYPICAL USES:

- Gypsum and cement wall boards
- Wood trim
- Concrete (poured and precast)
- Concrete Block
- Over alkyd paints

- Over glass, vinyl and many other difficult to paint surfaces
- Metal, steel alloys, aluminum etc.

## SURFACE

### PREPARATION:

Consult NPC representative for appropriate primers and base coats for specific applications.

All surfaces to be coated must be free of dirt, oils, laitance and any other contaminants, which may prevent proper adhesion.

Hard, glossy, non-porous surfaces should be mechanically abraded prior to coating application to improve adhesion.

## TECHNICAL DATA

<b>COLOUR:</b>	White or colours
<b>RESIN TYPE:</b>	Water-based Acrylic
<b>SHEEN:</b>	Gloss→Semi gloss
<b>PERCENT SOLIDS</b> by VOLUME:	33.7%
<b>WEIGHT PER GALLON:</b>	10.4 lbs/ U.S. gallon
<b>V.O.C.:</b>	100g/L
<b>THEORETICAL</b> <b>COVERAGE:</b>	540 sqft/US Gal @ 1 mil DFT
<b>RECOMMENDED DFT:</b>	1.8 mils per coat
<b>DRYING TIME</b> <b>@20°C(68°F):</b>	Touch Dry:-1 hour Recoat Time-2 hours
<b>REDUCER:</b>	Water
<b>CLEAN-UP</b>	Water